

Setting Environmental Variables

The default behaviour of TapeTrack programs can be changed by setting environmental variables.

These variables can be set using the following methods.

Windows Command Line

```
set VARIABLE=VALUE
```

Where VARIABLE is the variable name, and VALUE is the variable value.

Linux Shell

To set an environmental variable in the Linux operating system, use the `export` command.

```
export VARIABLE=VALUE
```

Where VARIABLE is the variable name, and VALUE is the variable value.

You can also prepend the variable to the command.

```
TMSSREPORTFORMAT=CSV TMSS10Inventory
```

TapeTrack Config File

The TapeTrack Config File that is loaded when each [Desktop](#) and [Command Line Program](#) is initiated, it can also be used to set [environmental variable](#).

```
variables = {  
    TMSSLEVELNAMES = "A,B,C";  
    TMSSNOLEVELSLOT = "1";  
};
```

Last update: 2025/01/21 22:07
technote:setting_environmental_variables https://rtfm.tapetrack.com/technote/setting_environmental_variables?rev=1553733944

From:
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:
https://rtfm.tapetrack.com/technote/setting_environmental_variables?rev=1553733944

Last update: **2025/01/21 22:07**

