

# Setting Environmental Variables

The default behaviour of TapeTrack programs can be changed by setting [environmental variable](#).

These [environmental variable](#) can be set using the following methods.

## Windows Command Line

```
set VARIABLE=VALUE
```

Where VARIABLE is the variable name, and VALUE is the variable value.

## Linux Shell

To set an [environmental variable](#) in the Linux operating system, use the export command.

```
export VARIABLE=VALUE
```

Where VARIABLE is the [environmental variable](#) name, and VALUE is the [environmental variable](#) value.

You can also prepend the [environmental variable](#) to the command.

```
TMSSREPORTFORMAT=CSV TMSS10Inventory
```

## TapeTrack Config File

The TapeTrack Config File that is loaded when each [Desktop](#) and [Command Line Program](#) is initiated, it can also be used to set [environmental variable](#).

```
variables = {  
    TMSSLEVELNAMES = "A,B,C";  
    TMSSNOLEVELSLOT = "1";  
};
```

Last  
update: 2025/01/21 22:07 technote:setting\_environmental\_variables [https://rtfm.tapetrack.com/technote/setting\\_environmental\\_variables?rev=1553734033](https://rtfm.tapetrack.com/technote/setting_environmental_variables?rev=1553734033)

---

From:  
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:  
[https://rtfm.tapetrack.com/technote/setting\\_environmental\\_variables?rev=1553734033](https://rtfm.tapetrack.com/technote/setting_environmental_variables?rev=1553734033)

Last update: **2025/01/21 22:07**

