

Setting Environmental Variables

The default behavior of TapeTrack programs can be changed by setting [environmental variable](#).

These [environmental variable](#) can be set using the following methods.

Windows Command Line

```
set VARIABLE=VALUE
```

Where VARIABLE is the [environmental variable](#) name, and VALUE is the [environmental variable](#) value.

PowerShell

To set an [environmental variable](#) in Windows PowerShell, use the env: command.

```
$env:TMSREPORTFORMAT = "CSV"
```

Using PowerShell variables will have no effect on TapeTrack executables.



Using a variable `$TMSREPORTFORMAT = "CSV"` will not be interpreted as a Windows variable and will not be applied to the output.

Linux Shell

To set an [environmental variable](#) in the Linux operating system, use the export command.

```
export VARIABLE=VALUE
```

Where VARIABLE is the [environmental variable](#) name, and VALUE is the [environmental variable](#) value.

You can also prepend the [environmental variable](#) to the command.

TMSSREPORTFORMAT=CSV TMSS10Inventory

TapeTrack Config File

The TapeTrack Config File that is loaded when each [Desktop](#) and [Command Line Program](#) is initiated, it can also be used to set [environmental variable](#).

```
variables = {  
    TMSSLEVELNAMES = "A,B,C";  
    TMSSNOLEVELSLOT = "1";  
};
```

From:
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:
https://rtfm.tapetrack.com/technote/setting_environmental_variables?rev=1565651426

Last update: **2025/01/21 22:07**

