Setting Environmental Variables

The default behavior of TapeTrack programs can be changed by setting environmental variable.

These environmental variable can be set using the following methods.

Windows Command Line

set VARIABLE=VALUE

Where VARIABLE is the environmental variable name, and VALUE is the environmental variable value.

PowerShell

To set an environmental variable in Windows PowerShell, use the env: command.

\$env:TMSSREPORTFORMAT = "CSV"



Using PowerShell variables will have no effect on TapeTrack executables.

Using a variable \$TMSSREPORTFORMAT = "CSV" will not be interpreted as a Windows variable and will not be applied to the output.

Linux Shell

To set an environmental variable in the Linux operating system, use the export command.

export VARIABLE=VALUE

Where VARIABLE is the environmental variable name, and VALUE is the environmental variable value.

You can also prepend the environmental variable to the command.

 $\label{local_problem} \begin{array}{l} \text{upgate:} \\ 2025/01/21 \end{array} \\ \text{technote:setting_environmental_variables https://rtfm.tapetrack.com/technote/setting_environmental_variables?rev=1565651426.} \\ \end{array}$

TMSSREPORTFORMAT=CSV TMSS10Inventory

TapeTrack Config File

The TapeTrack Config File that is loaded when each Desktop and Command Line Program is initiated, it can also be used to set environmental variable.

```
variables = {
    TMSSLEVELNAMES = "A,B,C";
    TMSSNOLEVELSLOT = "1";
};
```

https://rtfm.tapetrack.com/ - TapeTrack Documentation

Permanent link:

https://rtfm.tapetrack.com/technote/setting_environmental_variables?rev=156565142

Last update: 2025/01/21 22:07



https://rtfm.tapetrack.com/ Printed on 2025/12/01 06:48