

# Technical Note: TMSS10Volume Delete Examples

## Example - Delete Volumes From CSV List

### CSV File

```
100011L4  
100012L4  
100023L4  
100025L4  
100026L4
```

### TTIDEF File

Set CSV delimiter to comma, Customer-ID to US01, Media-ID to LTO and extract Barcode value from column one.

```
SetCSVDelimiter(",");  
  
SetLiteral(CUSTOMER, "US04");  
SetLiteral(MEDIA, "LTO");  
  
Extract(BARCODE, 1, 8, 0);
```

### Configuration File

Load Scanfile of Volume-ID's, traverse input file.  
If Volume-ID is present in the Scanfile delete Volume, if not skip Volume.

```
report =  
{  
    format = "csv";  
};  
traversal =  
{  
    scanfile= { file="default.ttidef"; };
```

```
customer =
(
  {
    id="*";
    media =
    (
      {
        id="*";
        volume =
        (
          {
            id="*";
            scanfile = true;
            skip=false;
          },
          {
            id="*";
            skip=true;
          }
        );
      }
    );
  }
);
};
```

## Command Line Syntax

```
TMSS10VolumeDelete -S user:-password@server -c master.cfg -l -r * <
volumes.csv
```

From: <https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link: <https://rtfm.tapetrack.com/technote/tmss10volumedelete?rev=1551740592>

Last update: **2025/01/21 22:07**

