

Technical Note: TMSS10Volume Delete Examples

Example - Delete Volumes From CSV List

CSV File

```
100011L4
100012L4
100023L4
100025L4
100026L4
```

TTIDEF File

Set CSV delimiter to comma, Customer-ID to US01, Media-ID to LTO and extract Barcode value from column one.

```
SetCSVDelimiter(",");

SetLiteral(CUSTOMER, "US04");
SetLiteral(MEDIA, "LTO");

Extract(BARCODE, 1, 8, 0);
```

Configuration File

Load Scanfile of Volume-ID's, traverse input file.
If Volume-ID is present in the Scanfile delete Volume, if not skip Volume.

```
report =
{
    format = "csv";
};
traversal =
{
    scanfile= { file="default.ttidef"; };
};
```

```
customer =  
(  
  {  
    id="*";  
    media =  
    (  
      {  
        id="*";  
        volume =  
        (  
          {  
            id="*";  
            scanfile = true;  
            skip=false;  
          },  
          {  
            id="*";  
            skip=true;  
          }  
        );  
      }  
    );  
  }  
);  
};
```

Command Line Syntax

```
TMSS10VolumeDelete -S user:-password@server -c master.cfg -l -r * <  
volumes.csv
```

From:
<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:
<https://rtfm.tapetrack.com/technote/tmss10volumedelete?rev=1551740592>

Last update: **2025/01/21 22:07**

