

Technical Note: TMSS10VolumeDelete Examples

Files needed to delete Volumes from a defined list from nominated Customer-ID and Media-ID.

Example - Delete Volumes From CSV List

CSV File

```
100011L4  
100012L4  
100023L4  
100025L4  
100026L4
```

TTIDEF File

Set CSV delimiter to comma, Customer-ID to US01, Media-ID to LTO and extract Barcode value from column one.

```
SetCSVDelimiter(",");  
  
SetLiteral(CUSTOMER, "US04");  
SetLiteral(MEDIA, "LTO");  
  
Extract(BARCODE, 1, 8, 0);
```

Configuration File

Load Scanfile of Volume-ID's, traverse input file.
If Volume-ID is present in the Scanfile delete Volume, if not skip Volume.

```
report =  
{  
    format = "csv";  
};  
traversal =
```

```
{
  scanfile= { file="default.ttidef"; };
  customer =
  (
    {
      id="*";
      media =
      (
        {
          id="*";
          volume =
          (
            {
              id="*";
              scanfile = true;
              skip=false;
            },
            {
              id="*";
              skip=true;
            }
          );
        }
      );
    }
  );
};
```

Command Line Syntax

Delete all volumes in volumes.csv from Customer-ID US01 and Media-ID LTO

```
TMSS10VolumeDelete -S user:-password@server -c master.cfg -l -r * <
volumes.csv
```

From: <https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link: <https://rtfm.tapetrack.com/technote/tmss10volumedelete?rev=1551741093>

Last update: **2025/01/21 22:07**

