TMSSCMDSTRING

The Environmental Variable TMSSCMDSTRING changes the behavior of Command Line Programs to take the value set in TMSSCMDSTRING and write that string, along with the variables to stdout.

This allows you to write commands automatically using the value TMSSCMDSTRING along with the values contained in the output from the Command Line Programs.

Example

Using TMSS10MoveList output as an example, the standard output displays Volume-ID, Current and Target location as well as move times and attributes.

```
System: TapeTrack
         Report ID: 102
Report Description: Moving Volumes List
      Report Notes: Customer(New York Data Center) Media Type()
   Production Time: Monday, April 20, 2020 - 12:35:59 (AUS Eastern Standard
Time)
      Report Width: 176 bytes
       Barcode
                            Current Location
                                                           Target Location
Seq.
Move Time
                Time
                                Container
     1 US01.LT0.210498JA
                            0FFS [28]
                                                          Library
2020-04-20 09:49
                       H2:46:48
     2 US01.LT0.210701JA
                            0FFS [37]
                                                          Library
2020-04-20 09:49
                       H2:46:48
     3 US01.LT0.210959JA
                            0FFS [43]
                                                          Library
2020-04-20 09:49
                       H2:46:48
     4 US01.LT0.211049JA
                            0FFS [46]
                                                          Library
2020-04-20 09:49
                       H2:46:48
            System: TapeTrack
         Report ID: 103
Report Description: Movement Directions Report
      Report Notes: Customer(New York Data Center) Media Type()
   Production Time: Monday, April 20, 2020 - 12:35:59 (AUS Eastern Standard
Time)
```

Last update: 2025/01/21 22:07

Report Width: 54 bytes			
Current Repository	Target Repository	Total	
ID(OFFS)	Library		4

When the Variable TMSSCMDSTRING is set before the execution of the Command Line program (in this example TMSS10MoveList) it modifies the output from the standard report, to that of a custom string that can include output variables.

Setting TMSSCMDSTRING to an ejection script for a TSM instance, listing all Volume-ID's that need to be ejected for processing and transport to the Vault.

set TMSSCMDSTRING=checkout libvol DC1_LIB0 \$volume-id checklabel=yes
remove=yes

environmental variables, reports, update doco

From:

https://rtfm.tapetrack.com/ - TapeTrack Documentation

Permanent link:

https://rtfm.tapetrack.com/variable/tmsscmdstring?rev=1587350678

Last update: 2025/01/21 22:07



https://rtfm.tapetrack.com/ Printed on 2025/12/01 10:42