

TMSSLEVELNAMES

TMSSLEVELNAMES allows, via configuration files or command line interface, to map zone levels numbers to string values.

Example

Using TMSS10Inventory to display LTO volumes currently as repository OFFS from customer US04.

```
TMSS10Inventory -S user:-password@server -V "US04.LTO.*@OFFS"
```

Output

```

                System: TapeTrack
Report Description: Inventory List
      Report Notes: Customer(Nashville Data Center) Media Type(LTO
Cartridge)
      Production Time: Monday, June 18, 2018 - 11:25:39 (AUS Eastern Standard
Time)
      Report Width: 161 bytes

```

Seq.	Barcode	Location	Repository
Next Move	Days	Last Move	GDup CDup Container
[1]	1 US04.LTO.000001L5	GT1 [1.1]	Offsite Vault
		2018-06-18 10:13	6 2
[2]	2 US04.LTO.000002L5	GT1 [1.2]	Offsite Vault
		2018-06-18 10:13	5 1
[3]	3 US04.LTO.000003L5	GT1 [1.3]	Offsite Vault
		2018-06-18 10:13	5 1
[5]	4 US04.LTO.000004L5	GT1 [1.5]	Offsite Vault
		2018-06-18 10:13	5 1

Setting TMSSLEVELNAMES to A, B, C before running TMSS10Inventory to change level names from 1, 2, 3 etc. TMSS10Inventory to display LTO volumes currently as repository OFFS from customer US04.

<sxh> set TMSLEVELNAMES=A,B,C

From:

<https://rtfm.tapetrack.com/> - **TapeTrack Documentation**

Permanent link:

<https://rtfm.tapetrack.com/variable/tmslevelnames?rev=1529285391>

Last update: **2025/01/21 22:07**

